

Deluxe

Size

- 2mm(T) x 300mm(W) x 300mm(L), 55Pcs/Box(4.95m²)
- Patterns without this sign are order based products
- 3mm(T) x 300mm(W) x 300mm(L), 37Pcs/Box(3.33m²)
- 3mm(T) x 450mm(W) x 450mm(L), 16Pcs/Box(3.24m²)

Uses

- Commercial Areas : Office, Factory, Etc.
- Public, Educational Facilities : School, Classroom, Library, Hospital, Church, etc.

Characteristics

- Highly economical and excellent in durability.
- Wear resistant, anti-discoloration and anti-distortion.
- Capable of creating unique areas with colorful marble chips.

Before Installation

- The subfloor should be marinated at the proper temperature before installation.
- The Subfloor must be fully dried out and free of any moisture.
- Any visible cracks on the floor must be repaired with sealant before installation.
- The subfloor must be free of dust, varnish, paint or any unevenness that might affect the adhesion or cause discoloration.

During Installation

- Please check whether the products have the same LOT number.
- Please make sure to read Cautions before installation.

► Adhesive recommendations

Type	Major Component	Open Time	Pot Life
Water-based	Acrylic	About 20~30min	3~6hr

After Installation

- Please maintain the room temperature from 18°C to 30°C for at least 24 hours after installation.
- Please use a roller, etc., to fully adhere the tiles to the floor within 5 hours after installation.
- Please avoid wax coating within 72 hours after installation.
- Stains can be removed with alcohol. Do not use acetone, thinner or other strong solvents to clean the product.

