

iD Spesso 55 / 70 Square Set 55 / 70

LUXURY VINYL TILES

**Stimulate
ambiances
with resistant
and large
vinyl tiles**



GREAT DESIGN, LASTING PERFORMANCE AND PRACTICAL AFFORDABILITY

iD Spesso & Square Set is the best duo to bring the full trifecta: great design, lasting performance and practical affordability.

GREAT VARIETY OF DESIGNS



These collections offer two new design families: the Classy Oak woods, a very pure and calm wood design and the Soft Terrazzo, a trendy neutral terrazzo. Our best-selling classics: Soft Oak, Primary Pine, Venezia and Cement design families are also reconducted. With a total of 20 designs, our new collections will support your vision for every space.

LASTING PERFORMANCE



Available in two wear layer thickness, 0.55 and 0.70mm our Collections meet Class 33 certification for heavy commercial use. Protected by our strong TopClean XP polyurethane coating, these authentic-looking LVT visuals help you create stylish, durable environments at a competitive price point.

TWO INSTALLATION METHODS POSSIBLE



iD Spesso enables a traditional and quick glue down installation while Square Set can be laid and take up again thanks to a special herringbone pattern. This collection is the best option for a reliable and fast renovation. Both collections come with 4 and 5mm thickness, enabling installation in a larger variety of subfloors.

A SUSTAINABLE SOLUTION



Through our Tarkett Human-Conscious Design® approach, we develop flooring that helps people flourish in their every day without compromising on health and the environment. With 90% of time spent indoors, clear air matters. Our LVT collections showcase ultra low VOC emissions, less than 100µg/m³ TVOC after 28 days. Our LVT is also phthalate-free. It contributes to healthier spaces and helps you reach green building certifications like WELL and LEED.



CAPTURING THE BEAUTY OF WOOD AND STONE

BRINGING THE OUTDOORS INSIDE

Nature guides every aspect of our design journey. We have carefully selected our 20 designs to replicate as good as possible the diversity that we find in nature. By selecting the best natural tones of wood and expressive stones, we have sought to bring the outdoors in.

The variety of our designs gives you the freedom to subtly match the style that best suits your space.

THE POWER OF NATURE

We aim to create positive emotions to help enhance learning, working and caring. iD Spesso & Square Set decors were selected to foster a feelgood atmosphere and bring interior designs to life. We are happy to provide two new design families: the Classy Oak wood, a very pure and calm wood designs and the Soft Terrazzo, a trendy neutral terrazzo.

A UNIQUE LARGE TILE FORMAT

To bring innovation and premium look, we designed the cement tiles in a large format of 91x91 cm, to better reproduce the large Terrazzo tiles.

For wood, for keep our most practical and best-selling format with 122 x 23cm.











Starters

Red Pepper soup	8
Almond, Mint & Ricotta Salad	14
Anchovies on Dried Tomatoes	16
Tuna and Lime Ceviche	16

Entrees

Californian Salmon Tartar	24
Sesame Tuna Steak	28
Fresh cod & Tomatillo Sauce	30
Black Angus Filet & Broccoli purée	34

Desserts

Pineapple Pie & Mango Sorbet	9
Chocolate Mousse Zabaglione	10
Mango Cheesecake	12
Vanilla Panna Cotta	12

Technical Datasheet Dry Back

Technical Data	Standards	iD Spesso 55
Classification	EN ISO 10582	Heterogeneous PVC floor covering
	EN ISO 10874	Domestic : 23 Commercial : 33
Wear Layer binder content	EN ISO 10582	Type I
Technical characteristics		
Total thickness	EN ISO 24346	5.00 mm
Wear layer thickness	EN ISO 24340	0.55 mm
Total weight	EN ISO 23997	9000 g/m ²
Bevelled edges	-	Microbevels
Surface treatment	-	Yes – TopClean XP
Form of delivery	EN ISO 24342 Plank (1219.2 x 228.6 mm)	5 planks / box (1.39m ²) 72 boxes/pallet (100.33 m ²)
	Tile (914.4 x 914.4 mm)	3 tiles / box (2.51m ²) 46 boxes/pallet (115.38 m ²)
Technical performance		
Dimensional stability	EN ISO 23999	≤ 0.25 %
Curl resultant to heat 6h at 80 °C (mm)	EN ISO 23999	≤ 2.00 mm
Reaction to fire	EN 13501-1	Bfl-s1
Residual Indentation	EN ISO 24343-1	≤ 0.10 mm
Castor chair	ISO 4918 (EN 425)	No damage
Furniture leg	EN 424	No damage
Light fastness	EN ISO 105-B02	≥ 6
Resistance to chemicals	EN ISO 26987 (EN 423)	Good resistance
Slip resistance	DIN 51130 EN 13893	R9 μ ≥ 0,30
Underfloor heating	-	Suitable – max. 27°C
VOC emission	ISO 16000	Gold (≤ 100 µg/m ³)
Recyclable	-	100%
Plasticizer	-	Phthalate-free
Commercial warranty	-	10 years
Colours	-	Wood: 11 Stones / Ceramic: 9

The above information is subject to modification for the benefit of further improvement (01/2024).
For the latest information, please visit our website: www.tarkett-asia.com
Tarkett's instructions regarding installation, cleaning and maintenance should be observed.





PROFLOORZ INTERNATIONAL PTE LTD

FOR MORE DETAILS

www.profloorz.asia | +65 6481 7160 | sales@profloorz.asia